PRODUCT
DATA
FILTER-LINE™
SERIES GRM
PD-FLGRM-03A
JANUARY 2003

AIR FILTERS

# FILTER-LINE™

# SERIES GRM

2" FIBERGLASS — STANDARD SCRIM BACKED ROLL MEDIA

# Description



The FILTER-LINE™ Series GRM — 2" Fiberglass Roll Media is produced from continuous strands of fiberglass. The media is a graded density blanket and all fiberglass strands are bonded by a thermo setting bonding agent. Media will yield a minimum thickness of 2 1/2" when unrolled in the air stream. The media is charged with a gel-type adhesive to effectively trap and hold dirt particles. The entire media blanket is reinforced by a fabric scrim netting, which maintains media configuration. The 65 feet long roll is provided with trailers and leaders for ease of installation. GRM Roll Media is available for all types of Roll Filter machines.

# Construction

#### **CONTINUOUS FIBERGLASS STRANDS**

Series GRM Media is continuous strands of fiberglass, thermo bonded to form media. Media has a dry weight of 14 to 18 grams per sq. ft. Each sq. ft. of media has @ 6.0 miles of fiberglass.

### **GRADED DENSITY MEDIA**

Series GRM Media is progressively denser from the air-entering to the air-leaving side. Fiber diameter begins at 50 microns on the clean side and reduces to 25 microns on the air-leaving side.

#### **GEL-TYPE ADHESIVE**

Series GRM Media is charged with an odorless, non-toxic gel adhesive. Each sq. ft. of media contains 12 to 16 grams. The gel is flameproof and will not flow at 150° F operating temperatures.

#### **FABRIC SCRIM NETTING**

Series GRM Media is fully supported on the downstream side of the media with a fabric scrim netting. This reinforcing backing is totally secured to the media and maintains media configuration.

#### MEDIA TRAILERS AND LEADERS

Series GRM Media is supplied with a heavy duty trailer and leader to assist in the installation of the Roll Media. Trailers and leaders are securely sewn to the GRM Media blanket.

#### **ASHRAE TESTED MEDIA**

Series GRM Media has been thoroughly tested by independent testing laboratories in strict accordance with current ASHRAE Standards for air filters. Test reports are available upon request.

#### Dimensional Data

AIRMAZE-TYPE			
MODEL NO. SIZE			
AIR20	20 1/2"		
AIR32	32 1/2"		
AIR44	44 1/2"		
AIR56	56 1/2"		
AIR68	68 1/2"		

CAMBRIDGE-TYPE			
MODEL NO.	SIZE		
CAM24	23 3/4"		
CAM33	32 3/4"		
CAM45	44 3/4"		
CAM57	56 3/4"		
CAM66	65 3/4"		
CAM69	68 3/4"		

FARR-TYPE			
MODEL NO.	SIZE		
FAR09	8 3/4"		
FAR15	14 3/4"		
FAR21	20 3/4"		
FAR27	26 3/4"		
FAR33	32 3/4"		
FAR39	38 3/4"		
FAR45	44 3/4"		
FAR51	50 3/4"		
FAR57	56 3/4"		
FAR69	68 3/4"		

AMERICAN-TYPE			
MODEL NO.	SIZE		
AME20	20 1/2"		
AME22	22 1/4"		
AME25	24 7/8"		
AME32	31 7/8"		
AME33	32 3/4"		
AME38	38 1/2"		
AME40	39 7/8"		
AME45	44 3/4"		
AME57	56 3/4"		
AME69	68 3/4"		

TRANE-TYPE			
MODEL NO.	SIZE		
TRA19	19 1/2"		
TRA21	21 1/8" 25 1/2" 31"		
TRA25			
TRA31			
TRA35	35"		
TRA38	38 3/8"		
TRA45	44 7/8"		
TRA50	49 3/4"		
TRA54	53 7/8"		
TRA59	58 3/4"		
TRA61	61 1/8"		
TRA63	62 3/4"		

BLC-TYPE			
MODEL NO.	SIZE		
BLC25	24 5/8"		
BLC35	34 5/8"		
BLC39	38 5/8"		
BLC47	46 5/8"		
BLC59	58 5/8"		
BLC71	70 5/8"		

<b>CONTINENTAL-TYPE</b>			
MODEL NO.			
CON22	21 7/8"		
CON32	31 7/8"		
CON36	35 7/8"		
CON44	43 7/8"		
CON56	55 7/8"		
CON68	67 7/8"		

<b>CARRIER-TYPE</b>			
MODEL NO.	SIZE		
CAR23	23 3/8"		
CAR26	26 1/4"		
CAR34	34 3/8"		
CAR37	37 1/4"		
CAR44	43 7/8"		
CAR47	47 1/4"		
CAR58	57 7/8"		
CAR61	61 1/4"		
CAR68	67 7/8"		

MINE SAFE	TY-TYPE
MODEL NO.	SIZE
MIN21	21"
MIN27	27"
MIN33	33"
MIN39	39"
MIN45	45"
MIN51	51"
MIN57	57"
MIN63	63"
MIN69	69"

#### MODEL NUMBER KEY FLGRMBLC47

Insert model number prefix to complete model number.

**FL-** FILTER-LINE™

GRM- Standard 2" Fiberglass Roll Media
BLC- BLC Industries, Inc. Type Core

47- Core Width

#### Note:

Trade names shown are used for reference purposes only.

Performanc			mance Data	3
SERIES	RESIS @ 300 FPM	TANCE @ 500 FPM	RECOMMENDED FINAL RESISTANCE	ARRESTANCE VALUE
GRM	.07	.14	.50	81%

# **Corporate Headquarters**

P.O. Box 14187, Louisville, Kentucky 40214 Phone: (502) 366-6002 Fax: (502) 366-6255 E-Mail: askus@blcind.com

# BLC-WEST

Phone: (480) 839-5333 Fax: (480) 839-1584

# www.blcind.com

We reserve the right to make changes in product design and product specifications without prior notice or obligation.



Breathe Easy, We Have The Line On Air Filtration.